


PULSAR ALUMINIUM 8W 220-240V 40°  **DIMMABLE LED EDISON**

UGR <16




MAC ADAM 3 STEP

IP65



IP20

Ø72mm



| CODE | COLOR | CCT | LUMENS | POWER | VOLTAGE | ANGLE | PF | A | Hz | LIFETIME | RA | IP |
|------|---------|---------|--------|-------|----------|-------|-------|-------|-------|----------|----|----|
| 4198 | ○ WHITE | 2.700 K | 780 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4199 | ○ WHITE | 3.000 K | 800 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4200 | ○ WHITE | 4.000 K | 840 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4217 | ○ WHITE | 5.000 K | 860 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4201 | ● BLACK | 2.700 K | 780 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4202 | ● BLACK | 3.000 K | 800 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4203 | ● BLACK | 4.000 K | 840 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |
| 4218 | ● BLACK | 5.000 K | 860 | 8W | 220-240V | 40° | > 0,9 | 0,037 | 50/60 | 30.000h | 85 | 65 |

