

New

LED luminaires

CEILINE III 10W / 15W / 20W / 25W / 30W



Ceiling luminaire

CEILINE III

10W (SLI022006WW, SLI022006NW, SLI022006CW)

15W (SLI022007WW, SLI022007NW, SLI022007CW)

20W (SLI022008WW, SLI022008NW, SLI022008CW)

25W (SLI022009WW, SLI022009NW, SLI022009CW)

30W (SLI022010WW, SLI022010NW, SLI022010CW)

Downlight luminaire mounted in the ceiling. Perfect for home, office, hotel or commercial purposes.

New

LED luminaires

CEILINE III 10W / 15W / 20W / 25W / 30W

Technical data

Product identifier	SLI022008NW
Length	
Width	
Suitable for wall mounting	No
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	Yes
Suitable for surface mounting	Yes
Control gear included	Yes
Nominal voltage	220-240 V
Nominal current	90 mA
System power	20 W
Colour temperature	3600-4800 K
Material housing	Plastic
Colour housing	White
Radiation angle	Extreme wide beam >80°
Height/depth	90 mm
Outer diameter	190 mm
Degree of protection (IP)	IP20
Ambient temperature	-20, 40 °C
Effective luminous flux	1600 lm
Colour rendering index CRI	80-89

Remaining photos:

New

LED luminaires

CEILINE III 10W / 15W / 20W / 25W / 30W

