



UFO ALUMINIUM 300W 100-260V 110° LED PHILIPS



INVERTRONICS DRIVER  
LED TYPE SMD  
**PHILIPS**

2M CABLE  
POLYCARBONATE COVER  
ANTI IMPACTS



**MULTI  
TENSION**


CODE	CCT	LUMENS	CD	POWER	VOLTAGE	ANGLE	PF	A	Hz	LIFETIME	RA	IP
3972	4.000 K	39.000	14.000	300W	100-260V	110°	> 0,9	1,3	50/60	50.000h	80	65





## LIRA UFO 100W-150W-200W-240W





IP65




 Dank des Dissipationsystems wird die Leistung und die Lebensdauer der LED verbessert.


 Thanks to its dissipation system improves the performance and the useful life of the LED's.

 Grâce au système de dissipation de chaleur la led améliore son efficacité énergétique et sa durée de vie.


 Grazie al suo sistema di dissipazione il rendimento e la vita del LED's migliorano.

 Gracias a su sistema de disipación mejora el rendimiento y la vida útil de los LED's.

LIRA 100W - 150W - 200W  
CODE 3798



LIRA 240W  
CODE 3799



### INVERTRONICS DRIVER



RoHs



SELV



Spannungsbereich 90 ~ 305 Vac, Überspannungsschutz (OVP), Überhitzungsschutz (OTP) und Kurzschlusschutz (SCP).



Voltage range is 90~305 Vac, with over-voltage protection (OVP), over-temperature protection (OTP) and short-circuit protection (SCP).



Gamme de tension de 90 ~ 305 Vac, protection contre les surtensions (OVP), protection contre la surchauffe (OTP) et la protection contra courts-circuits (SCP).



Campo di tensione di 90 ~ 305 Vac, protezione da sovratensione (OVP), protezione termica (OTP) e cortocircuito (SCP).



Rango de voltaje de 90 ~ 305 Vac, protección contra sobretensión (OVP), protección contra sobretemperatura (OTP) y protección contra cortocircuitos (SCP).