

11
Watt

LED
True Color
RGB

CC
V₊ V₋ I₊ I₋

IP 20

CE

EMC

M

M


F

t_a -10° ÷ +40°C


House icon

III

50 mm



Full Color P5 II Led



TRIO P MR 16
Diffused

Spot a LED di potenza - 3 x 3 x 350mA

- Si adatta ai faretto da incasso per lampadina dicroica Ø 50mm
- Fornito con cavo CB064, 30 cm, connettori AMP, 4 poli (M/F)
- LED utilizzati: 3 x FULL COLOR P5 II.

High Brightness LED spot - 3 x 3 x 350mA

- Suitable for being built in standard Ø 50mm downlights
- Delivered with CB064 lead, 30 cm 4 pins cables (M/F) with AMP connectors
- Fitted with 3 x FULL COLOR P5 II.

High Brightness LED-Spot - 3 x 3 x 350mA

- Für Einbau in Ø 50mm Einbaustrahler geeignet
- Geliefert mit Cb064 Kabel, 30 cm 4polige Kabel (M/F) mit AMP-Stecker
- Mit 3 LED Typ FULL COLOR P5 II

Spot à LED de puissance - 3 x 3 x 350mA

- Adaptable dans les spots encastrables pour lampes dichroïques Ø 50mm
- Livré équipé du câble CB064, 30 cm, connecteurs AMP, 4 pôles (M/F)
- Equipé de 3 LED du type FULL COLOR P5II

Foco a LED de potencia - 3 x 3 x 350mA

- Adaptable en los focos empotrables para lámparas dicroicas de Ø 50mm
- Suministrado con cable CB064, 30 cm, conectores 4 polos (M/F)
- Equipado de 3 LED del tipo FULL COLOR P5 II

Part number	Colour	Lumen Typ.	Beam	Lux at 1 m	I (typ.)	V (typ.)	W (typ.)	Ø	Standard Size
A40TRIOCPW00	RGB	315	Wide 40°	630	3x350mA	11,5V	11W	50 mm	MR16
A40TRIOCPM00	RGB	315	Medium 25°	920	3x350mA	11,5V	11W	50 mm	MR16
A40TRIOCP500	RGB	315	NO Lens 110°	75	3x350mA	11,5V	11W	50 mm	MR16

